AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1 - 15. (Cancelled)

16. (Currently Amended) A liquid crystal arrangement discharging method for discharging liquid crystal from a discharge unit to arrange the liquid crystal on a substrate on which a plurality of pixel regions composed of a plurality of pixels are formed, in which the discharge unit comprises including a plurality of nozzles for discharging the liquid crystal in a form of liquid droplets, the liquid crystal arrangement method comprising:

determining an arrangement pitch of the liquid droplets to be arranged in line on the substrate based on a diameter of the liquid droplets after impact of the liquid droplets on the substrate, which was measured in advance;

measuring a weight of the single liquid droplet for obtaining said diameter; and discharging the liquid droplets from the nozzles such that each of the liquid droplets has said weight and maintains the arrangement pitch and thereby the diameter of the liquid droplets after impact is roughly equal to the arrangement pitch of the plurality of pixel regions, and each of the plurality of pixel regions is coated with the liquid droplets.

17. (Currently Amended) The liquid crystal arrangement discharging method according to claim 16, wherein the arrangement pitch of the liquid droplets is roughly equal to the diameter of the liquid droplets after impact.

18-19 (Cancelled)

20. (Currently Amended) A liquid crystal arrangement discharging device comprising:

a discharge unit for discharging liquid crystal to arrange the liquid crystal on a substrate on which a plurality of pixel regions composed of a plurality of pixels are formed, the discharge unit comprising a plurality of nozzles which discharge the liquid crystal in a form of liquid droplets;

a weight measurement device which measures a weight of the single liquid droplet; and

a controller that controls an interval between the liquid crystal discharged from the nozzles based on a diameter of the liquid droplets after impact of the liquid droplets on the substrate, which was measured in advance, wherein

said discharge unit discharges the liquid droplets from the nozzles such that each of the liquid droplets has said weight and maintains the intervalthereby the diameter of the liquid droplets after impact is roughly equal to the arrangement pitch of the plurality of pixel regions, and each of the plurality of pixel regions is coated with the liquid droplets.

- 21. (Cancelled)
- 22. (Currently Amended) The liquid crystal arrangement-discharging device according to claim 20, comprising:
 - a plurality of pixel regions arranged on the substrate, and

a drive system for moving the nozzle and the substrate relative to each other and aligning each impact location of the liquid droplets with each location of the pixel regions.

23 - 26. (Cancelled)

27. (Currently Amended) The liquid crystal arrangement discharging method according to claim 16, wherein

the arrangement pitch is obtained by selecting <u>a subset of</u> the nozzles having a pitch therebetween equal to the arrangement pitch, <u>among the plural nozzles</u>.

28. (Currently Amended) The liquid crystal arrangement-discharging device according to claim 20, wherein

the controller controls the interval by selecting the nozzles having a pitch therebetween equal to the arrangement pitch, among the plural nozzles.